

NYLOTUF SPECIFICATIONS

3 STRAND POLYAMIDE MULTI-FILAMENT ROPE CONFIRMS TO IS 4572-2014

Diameter		Circumference	Runnage	Weight/220 Mtrs. Coil	Minimum Breaking Load
(mm)	(Inch)	(Inch)	(Mtrs./Kgs)	(Kgs)	(KGF)
6	1/4"	3/4"	44.44	4.95	750
8	5/16"	1"	25.00	8.80	1345
10	3/8"	1 1/8"	16.17	13.60	2088
12	1/2"	1 1/2"	11.22	19.60	2995
14	9/16"	1 3/4"	8.20	26.80	4095
16	5/8"	2"	6.28	35.00	5300
18	3/4"	2 1/4"	5.00	44.00	6695
20	13/16"	2 1/2"	4.07	54.00	8300
22	7/8"	2 3/4"	3.33	66.00	10000
24	1"	3"	2.82	78.00	12000
26	1 1/16"	3 1/4"	2.38	93.40	13950
28	1 1/8"	3 1/2"	2.05	107.00	15800
30	1 1/4"	3 3/4"	1.80	122.10	17755
32	1 5/16"	4"	1.58	139.00	20000
36	1 7/16"	4 1/2"	1.25	176.00	24900
40	1 5/8"	5"	1.00	218.00	30000
44	1 3/4"	5 1/2"	0.83	264.00	35800
48	2"	6"	0.70	312.00	42000